


**GESCHAKELDE VOEDING SINGLE OUTPUT 75W 12V/6.3A PFC**

**€ 47,89**

Excl. BTW: € 39,58

**Afbeeldingen**



**Beschrijving**

**Technical Specifications**

Input Voltage:	85...264V AC (47...63Hz)
	120...370V DC
Input Inrush Current, Max.:	35A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	-5/+10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3750V AC

I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-25...+70°C
Weight:	440g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
RSP-75-3.3	3,3	0...15	49,5	2	80	76
RSP-75-5	5	0...15	75	2	80	82
RSP-75-7.5	7,5	0...10	75	2	80	84
RSP-75-12	12	0...6,3	75,6	2	120	85
RSP-75-13.5	13,5	0...5,6	75,6	2	120	85
RSP-75-15	15	0...5	75	2	120	86
RSP-75-24	24	0...3,2	76,8	1	120	87
RSP-75-27	27	0...2,8	75,6	1	120	88
RSP-75-48	48	0...1,6	76,8	1	200	89

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

Artikelnummer	RSP7512
Merk	MEANWELL

