

GESCHAKELDE VOEDING SINGLE OUTPUT 36W 36V/1A

€ 16,95

Excl. BTW: € 14,01

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low profile
- Safety standards: EN 62368-1
- EMC standards: EN 55032 Class B and more
- 3 years manufacturer warranty



Technical Specifications



Input Voltage:	85...264V AC (47...63Hz)
	120...373V DC
Input Inrush Current, Max.:	45A
Leakage Current, Max.:	0,75mA
Output Voltage Adjustment:	±10%
Over Load Protection:	110...150%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	1250V AC
Operating Temperature:	-30...+70°C
Operating Altitude, Max.:	5000m
Weight:	230g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U _A	I _A	P _A	DU _A	U _{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
LRS-35-5	5	0...7	35	2	80	82
LRS-35-12	12	0...3	36	1	120	86

LRS-35-15	15	0...2,4	36	1	120	86
LRS-35-24	24	0...1,5	36	1	150	88
LRS-35-36	36	0...1	36	1	200	88
LRS-35-48	48	0...0,8	38,4	1	200	89

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	LRS3536
Merk	MEANWELL

