

NIMH-LADER 1-4 X AAA/AA

€ 22,95

Excl. BTW: € 18,97

Afbeeldingen



Beschrijving

Features

- Intelligent "PERFECT 7" charging technology (fully automatic 7-step charging process): Capacity quick test, Gentle pre-charging, Battery analysis, Quick charge, IQ switch-off, Top-off charge, Trickle charge maximises the life and the performance of the batteries considerably
- Quick capacity test determines the remaining charge of the battery and displays it on the LED panel for 5 seconds
- Gentle precharging with a lower current for weak or deeply discharged battery
- Battery Analysis and evaluation for a reliably usage or to determine a defect of a battery
- Fast charging mode saves idle time and also allows to get by with fewer batteries overall
- IQ switch-off protect the inserted batteries from overheating and overcharging
- Top-off charging ensures that the battery is gently charged to 100% full
- The battery is kept in a fully charged state by means of charging pulses
- Microcontroller controlled charging with single shaft monitoring
- Automatic start of charging and charging current adjustment after inserting the battery with the correct polarity
- Status display by means of 3-colour LED per charging bay
- Compact design
- Connection possible via Powerbank or via USB

Technical Specifications

| | |
|------------------------------|---------|
| Input Voltage: | 5V DC |
| Fastest Charging, Min.: | 1.000mA |
| Fastest Charging, Max.: | 2.400mA |
| Charge Current | |
| For Battery Size AA, D, C: | 800mA |
| For Battery Size AAA: | 400mA |
| For Battery Size 9V E-Block: | 15mA |
| Trickle Charge Current | |
| For Battery Size AA D, C: | 13mA |
| For Battery Size AAA: | 6,5mA |
| For Battery Size 9V E-Block: | 1,3mA |

Dimensions and Weight

| Part No. | Dimensions | Weight |
|-----------|------------|--------|
| | [mm] | [g] |
| 1001-0091 | 42x97x29 | 48 |

| | | |
|-----------|------------|-----|
| 1001-0092 | 72x97x29 | 76 |
| 1001-0093 | 150x152x47 | 315 |

Selection table Rechargeable Batteries

| Battery Size | Number of Cells | Chargeable Capacity, Max. |
|--------------|-----------------|---------------------------|
| [NiHM] | [NiHM] | [mAh] |
| AA | 1-4 | 3.000 |
| AAA | 1-4 | 1.100 |

Charging Data

| Battery Size | Capacity | Charge Time | Charge Current |
|--------------|----------|-------------|----------------|
| [NiHM] | [mAh] | [h] | [mA] |
| AAA | 1.000 | 3 | 400 |
| AAA | 800 | 2,4 | 400 |
| AA | 2.650 | 4 | 800 |
| AA | 2.500 | 3,75 | 800 |
| AA | 2.100 | 3 | 800 |
| AA | 1.300 | 2 | 800 |

Productinformatie

| | |
|---------------|-----------|
| Artikelnummer | 1001-0092 |
| Merk | ANSMANN |
| Is on Sale | Nee |

