


GESCHAKELDE VOEDING SINGLE OUTPUT 50W 12V/4.2A

€ 21,95

Excl. BTW: € 18,14

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low profile
- Safety standards: EN 62368-1
- EMC standards: EN 55032 Class B and more
- 3 years manufacturer warranty

Technical Specifications

Input Voltage:

85...264V AC (47...63Hz)

120...373V DC

Input Inrush Current, Max.:	45A
Leakage Current, Max.:	0,75mA
Output Voltage Adjustment:	±10%
Over Load Protection:	110...150%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	1250V AC
Operating Temperature:	-30...+70°C
Operating Altitude, Max.:	5000m
Weight:	230g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
LRS-50-3.3	3,3	0...10	33	3	80	80
LRS-50-5	5	0...10	50	2	80	83
LRS-50-12	12	0...4,2	50,4	1	120	86
LRS-50-15	15	0...3,4	51	1	120	88
LRS-50-24	24	0...2,2	52,8	1	150	88
LRS-50-36	36	0...1,45	52,2	1	200	89
LRS-50-48	48	0...1,1	52,8	1	200	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	LRS5012
Merk	MEANWELL

