


GESCHAKELDE VOEDING 156W 36V/4,3A

€ 29,95

Excl. BTW: € 24,75

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- LRS-150F: Universal input
- LRS-150: 230V AC/115V AV by switch
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage/ over temperature
- Low profile
- Safety standards: EN 62368-1
- EMC standards: EN 55032 Class B and more
- 3 years manufacturer warranty

Technical Specifications

Input Voltage

LRS-150F:	85...264V AC (47...63Hz)
	120...370V DC
LRS-150:	85...132V AC/170...264V AC (47...63Hz)
	240...370V DC
Input Inrush Current, Max.:	60A
Leakage Current, Max.:	0,75mA
Output Voltage Adjustment:	±10%
Over Load Protection:	110...140%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	1250V AC
Operating Temperature:	-30...+70°C
Operating Altitude, Max.:	5000m
Weight:	480g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
LRS-150F-5	5	0...22	110	2	100	85
LRS-150F-12	12	0...12,5	150	1	150	87,5
LRS-150F-15	15	0...10	150	1	150	89
LRS-150F-24	24	0...6,5	156	1	200	89
LRS-150F-36	36	0...4,3	154,8	1	200	89
LRS-150F-48	48	0...3,3	158,4	1	200	90
LRS-150-12	12	0...12,5	150	1	150	87,5
LRS-150-15	15	0...10	150	1	150	88,5

LRS-150-24	24	0...6,5	156	1	200	89
LRS-150-36	36	0...4,3	154,8	1	200	89
LRS-150-48	48	0...3,3	158,4	1	200	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	LRS15036
Merk	MEANWELL

