
GESCHAKELDE VOEDING SINGLE OUTPUT 480W 24V/20A

€ 159,50

Excl. BTW: € 131,82

Afbeeldingen



Beschrijving

Universal AC input / Full range
Built in active PFC function, PF>0.95
Protections: Short circuit / Overload / Over voltage / Over temperature
Forced air cooling by built-in DC fan
High power density 5.18w/in
Low profile:43mm thickness
Built-in remote ON-OFF control
Built-in remote sense function
Active AC surge current limiting

MODEL SP-480-24

OUTPUT:

DC VOLTAGE 24V

RATED CURRENT 20A

CURRENT RANGE 0 ~ 22A

RATED POWER 480W

RIPPLE & NOISE (max.) 150mVp-p

OUTPUT VOLTAGE ADJ. RANGE 22 ~ 27.6V

VOLTAGE TOLERANCE +/-1.0%
LINE REGULATION +/-0.2%
LOAD REGULATION +/-0.5%
SETUP, RISE TIME 1000ms, 80ms at full load
HOLD TIME (Typ.) 18ms at full load

INPUT:

VOLTAGE RANGE 85 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 87%
AC CURRENT (Typ.) 3.5A/230VAC
INRUSH CURRENT (Typ.) 40A/230VAC
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 23.1 ~ 29.7A rated output power
OVER VOLTAGE 28.8 ~ 33.6V Protection type : Shut down o/p voltage, re-power on to recover.

Dimensions 278*127*43mm (L*W*H)

Productinformatie

Artikelnummer	SP48024
Merk	MEANWELL
Is on Sale	Nee

