


## TUIMEL 2 X WISSEL 3ST 10A MET 6,3MM FASTON AANSLUITING

€ 24,50

Excl. BTW: € 20,25

### Afbeeldingen



### Beschrijving

#### Features

- For central mounting
- Metal rocker arm
- Approved up to 250V/10A

#### Selection Table

| Part Nr. | Nr. of Poles | Function          |
|----------|--------------|-------------------|
| KN3002   | 1-Pole       | 1 x On-On         |
| KN3012   | 2-Pole       | 2 x On-On         |
| KN3001   | 1-Pole       | 1 x On-Off        |
| KN3011   | 2-Pole       | 2 x On-Off        |
| KN3003   | 1-Pole       | 1 x On-Off-On     |
| KN3013   | 2-Pole       | 2 x On-Off-On     |
| KN3004   | 1-Pole       | 1 x (On)-Off-(On) |

|        |        |                   |
|--------|--------|-------------------|
| KN3014 | 2-Pole | 2 x (On)-Off-(On) |
|--------|--------|-------------------|












## Technical Specifications

|  |                      |
|--|----------------------|
| Operating Voltage, Max.:                   | 250V AC              |
| Switching Current, Max.:                   | 10A                  |
| Switching Current C3900, C3950:            | 16A                  |
| Switching Current at Inductive Load, Max.: | 4A                   |
| Ambient Temperature, Max.:                 | 85°C                 |
| Insulation Resistance:                     | >20MΩ                |
| Contact Resistance                         |                      |
| (New State, 12V DC/1A):                    | <100mΩ               |
| Contact Opening Width:                     | 3mm                  |
| Soldering Conditions (Hand Solder):        | 350°C/6s             |
| Materials                                  |                      |
| Shell:                                     | Nylon 6.6            |
| Lever:                                     | Brass, Nickel-plated |
| Current-carrying Part:                     | Cu Alloy             |
| Contacts:                                  | Silver-plated        |
| Flammability Class:                        | UL94V2               |

## Panel Cut-out

|               |         |
|---------------|---------|
| Wall Strength | Cut-out |
| [mm]          | [mm]    |
| 4,0           | Ø 12,7  |

## Approvals

 O5: 10 (4)A, 250Vac, T85  
C3900, C3950:  O5: 16 (4)A, 250Vac, T85  
  20A 125/277Vac (on-off circuits)  
  16A 125/277Vac (other circuits)  
  7A 72Vdc, 14A 36Vdc  
 250Vac 1hp, 125Vac 1/2hp  
 85°C, file E45221,  file LR10990

## Productinformatie

|               |             |
|---------------|-------------|
| Artikelnummer | KN3013      |
| Merk          | ARCOLECTRIC |

