


**TUIMEL 2 X WISSEL 3ST TOGGLE 10A MET 6,3MM FASTON AANSLUITING**

**€ 17,25**

Excl. BTW: € 14,26

**Afbeeldingen**



**Beschrijving**

**Features**

- For central mounting
- Metal rocker arm
- Approved up to 250V/10A

**Selection Table**

Part Nr.	Nr. of Poles	Function
KN3002	1-Pole	1 x On-On
KN3012	2-Pole	2 x On-On
KN3001	1-Pole	1 x On-Off
KN3011	2-Pole	2 x On-Off
KN3003	1-Pole	1 x On-Off-On
KN3013	2-Pole	2 x On-Off-On
KN3004	1-Pole	1 x (On)-Off-(On)

KN3014	2-Pole	2 x (On)-Off-(On)
--------	--------	-------------------












## Technical Specifications

Operating Voltage, Max.:	250V AC
Switching Current, Max.:	10A
Switching Current C3900, C3950:	16A
Switching Current at Inductive Load, Max.:	4A
Ambient Temperature, Max.:	85°C
Insulation Resistance:	>20MΩ
Contact Resistance	
(New State, 12V DC/1A):	<100mΩ
Contact Opening Width:	3mm
Soldering Conditions (Hand Solder):	350°C/6s
Materials	
Shell:	Nylon 6.6
Lever:	Brass, Nickel-plated
Current-carrying Part:	Cu Alloy
Contacts:	Silver-plated
Flammability Class:	UL94V2

## Panel Cut-out

Wall Strength	Cut-out
[mm]	[mm]
4,0	Ø 12,7

## Approvals

 05: 10 (4)A, 250Vac, T85  
C3900, C3950:  05: 16 (4)A, 250Vac, T85  
  20A 125/277Vac (on-off circuits)  
  16A 125/277Vac (other circuits)  
  7A 72Vdc, 14A 36Vdc  
 250Vac 1hp, 125Vac 1/2hp  
 85°C, file E45221,  file LR10990

## Productinformatie

Artikelnummer	KN3014
Merk	ARCOLECTRIC

