


DIN-RAIL VOEDING 70MM 92W 15V/6,13A

€ 36,95

Excl. BTW: € 30,54

Afbeeldingen



Beschrijving

Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Low no load power consumption
- Power-on LED display
- Insulation Class II

Technical Specifications

Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

Input Inrush Current, Max.:	70A
Over Load Protection	
HDR-100_:	102...110%
HDR-100_N:	105...150%
Withstand Voltage, I/P-O/P:	4000V AC
Operating Temperature:	-30...+70°C
Weight:	270g

I/P = Input, O/P = Output

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
HDR-100-12	12	0...7,1	85,2	2	120	88
HDR-100-15	15	0...6,13	92	1	120	89
HDR-100-24	24	0...3,83	92	1	150	90
HDR-100-48	48	0...1,92	92,2	1	240	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	HDR10015
Merk	MEANWELL

