



Zanderijweg 12,  
6717BM Ede  
T. 0318-757900

## GESCHAKELDE VOEDING SINGLE OUTPUT 72W 12V/6A

€ 31,50

Excl. BTW: € 26,03

### Afbeeldingen



### Beschrijving

MODEL RS-75-12

OUTPUT:

DC VOLTAGE 12V

RATED CURRENT 6A

CURRENT RANGE 0 ~ 6A

RATED POWER 72W

RIPPLE & NOISE (max.) 120mVp-p

OUTPUT VOLTAGE ADJ. RANGE 10.8 ~ 13.2V

VOLTAGE TOLERANCE +/-1.0%  
LINE REGULATION +/-0.5%  
LOAD REGULATION +/-0.5%  
SETUP, RISE TIME 500ms, 30ms/230VAC  
HOLD TIME (Typ.) 60ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC  
FREQUENCY RANGE 47 ~ 63Hz  
EFFICIENCY(Typ.) 81%  
AC CURRENT (Typ.) 1.2A/230VAC  
INRUSH CURRENT (Typ.) COLD START 40A/230VAC  
LEAKAGE CURRENT

PROTECTION:

OVER LOAD 110 ~ 150% rated output power  
Protection type : Hiccup mode, recovers automatically after fault condition is removed  
OVER VOLTAGE 13.8 ~ 16.2V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 129\*97\*38mm (L\*W\*H)



**EIJLANDER**  
the best in electronics!

## Productinformatie

---

Artikelnummer	RS7512
Merk	MEANWELL
Is on Sale	Nee

