


DIN-RAIL 40MM VOEDING 120W 24V/2.5A

€ 37,93

Excl. BTW: € 31,35

Afbeeldingen



Beschrijving

Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- DC OK LED display

Technical Specifications

Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Typ.:	35A

Leakage Current, Max.:	1mA
Output Voltage Adjustment:	+15%
Over Load Protection:	105...130%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	600g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
NDR-120-12	12	0...10	120	2	100	85,5
NDR-120-24	24	0...5	120	1	120	88
NDR-120-48	48	0...2,5	120	1	150	89

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	NDR12048
Merk	MEANWELL

