


## DIN-RAIL 17.5MM VOEDING 15W 48V/0.32A

€ 15,95

Excl. BTW: € 13,18

### Afbeeldingen



### Beschrijving

#### Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Low no load power consumption
- Power-on LED display
- Insulation Class II



#### Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

|                             |             |
|-----------------------------|-------------|
| Input Inrush Current, Max.: | 45A         |
| Over Load Protection:       | 110...145%  |
| Withstand Voltage, I/P-O/P: | 4000V AC    |
| Operating Temperature:      | -30...+70°C |
| Weight:                     | 78g         |

I/P = Input, O/P = Output



| Part Nr.  | $U_A$ | $I_A$    | $P_A$ | $DU_A$ | $U_{RN}$             | $h$  |
|-----------|-------|----------|-------|--------|----------------------|------|
|           | [V]   | [A]      | [W]   | [%]    | [mV <sub>p-p</sub> ] | [%]  |
| HDR-15-5  | 5     | 0...2,4  | 12    | 2      | 80                   | 80   |
| HDR-15-12 | 12    | 0...1,25 | 15    | 1      | 120                  | 85   |
| HDR-15-15 | 15    | 0...1    | 15    | 1      | 120                  | 85,5 |
| HDR-15-24 | 24    | 0...0,63 | 15,2  | 1      | 150                  | 86   |
| HDR-15-48 | 48    | 0...0,32 | 15,4  | 1      | 240                  | 87   |

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Productinformatie

|               |          |
|---------------|----------|
| Artikelnummer | HDR1548  |
| Merk          | MEANWELL |

