


## DIN-RAIL 35MM VOEDING 30W 48V/0.75A

€ 19,95

Excl. BTW: € 16,49

### Afbeeldingen



### Beschrijving

#### Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Low no load power consumption
- Power-on LED display
- Insulation Class II

#### Technical Specifications

Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

|                             |             |
|-----------------------------|-------------|
| Input Inrush Current, Max.: | 45A         |
| Over Load Protection:       | 105...160%  |
| Withstand Voltage, I/P-O/P: | 3000V AC    |
| Operating Temperature:      | -30...+70°C |
| Weight:                     | 120g        |

I/P = Input, O/P = Output

| Part Nr.  | $U_A$ | $I_A$    | $P_A$ | $DU_A$ | $U_{RN}$             | h   |
|-----------|-------|----------|-------|--------|----------------------|-----|
|           | [V]   | [A]      | [W]   | [%]    | [mV <sub>p-p</sub> ] | [%] |
| HDR-30-5  | 5     | 0...3    | 15    | 2      | 80                   | 82  |
| HDR-30-12 | 12    | 0...2    | 24    | 1      | 120                  | 88  |
| HDR-30-15 | 15    | 0...2    | 30    | 1      | 120                  | 89  |
| HDR-30-24 | 24    | 0...1,5  | 36    | 1      | 150                  | 89  |
| HDR-30-48 | 48    | 0...0,75 | 36    | 1      | 240                  | 90  |

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

|               |          |
|---------------|----------|
| Artikelnummer | HDR3048  |
| Merk          | MEANWELL |

