

LITHIUM 3.6V 8500MA C 26/2X50.5MM

€ 22,25

Excl. BTW: € 18,39

## Afbeeldingen



## Beschrijving

### Features

- High energy density
- Long term high performance
- Higher voltage under pulse load even with low background currents
- Improved voltage delay behaviour at ambient and elevated temperatures
- Fast voltage recovery after long term storage
- More capacity
- Higher discharge rate
- No orientation effect
- Wide temperature range from -55°C to +85°C
- SL-\_/S: Standard version
- SL-\_/T: Solder lugs
- SL-\_/P: Axial connection

## Technical Specifications

System:	LiSOCl <sub>2</sub>
Nominal Voltage:	3,6V
Temperature Range:	-55...+85°C

Part No.	Cell Size	C <sub>N</sub> [mAh]	I <sub>N</sub> [mA]	I <sub>max.</sub> [mA]	I <sub>p</sub> [mA]
SL-750/S	1/2AA	1100	1	50	100
SL-761/S	2/3AA	1500	1,3	75	150
SL-760/S	AA	2200	2	100	200
SL-2770/S	C	8500	3	230	400
SL-2780/S	D	19000	4	340	600

C<sub>N</sub> = Nominal Capacity, I<sub>N</sub> = Nominal Current, I<sub>max.</sub> = Continuous Discharge Current, max., I<sub>p</sub> = Pulse Current Capability

## Productinformatie

---

Artikelnummer	SL2770/S
Merk	TADIRAN

