

## LITHIUM 3.6V 1200MA 1/2AA 14.1X25MM AXIALE AANSLUITING

€ 9,24

Excl. BTW: € 7,64

### Afbeeldingen



### Beschrijving

#### Features

- Extremely low self-discharge (1% or less per year)
- High energy density
- Suited for long-term use with low current
- For operation at low current levels with long stands
- Intermittent discharge with medium current level provided the average is not below
- Wide temperature range from -55°C to +85°C
- Excellent shelf life (10 years)
- SL-\_/S: Standard version
- SL-\_/T: Solder lugs
- SL-\_/P: Axial connection

#### Technical Specifications

System:	LiSOCl <sub>2</sub>
Nominal Voltage:	3,6V
Temperature Range:	-55...+85°C
Shelf Life:	10 Years

Part No.	Cell Size	C <sub>N</sub> [mAh]	I <sub>N</sub> [mA]	I <sub>max.</sub> [mA]
SL350/S	1/2AA	1200	0,6	6
SL350/T	1/2AA	1200	0,6	6
SL350/P	1/2AA	1200	0,6	6
SL361/S	2/3AA	1600	1	10
SL361/T	2/3AA	1600	1	10
SL360/S	AA	2400	2	20
SL360/T	AA	2400	2	20
SL360/P	AA	2400	2	20

C<sub>N</sub> = Nominal Capacity, I<sub>N</sub> = Nominal Current, I<sub>max.</sub> = Continuous Discharge Current, max.

## Productinformatie

Artikelnummer	SL350/P
Merk	TADIRAN

