

LITHIUM 3.6V 2400MA AA 14.7X50.5MM

€ 8,95

Excl. BTW: € 7,40

Afbeeldingen



Beschrijving

Features

- Extremely low self-discharge (1% or less per year)
- High energy density
- Suited for long-term use with low current
- For operation at low current levels with long stands
- Intermittent discharge with medium current level provided the average is not below
- Wide temperature range from -55°C to +85°C
- Excellent shelf life (10 years)
- SL-_/S: Standard version
- SL-_/T: Solder lugs
- SL-_/P: Axial connection

Technical Specifications

System:	LiSOCl ₂
Nominal Voltage:	3,6V
Temperature Range:	-55...+85°C
Shelf Life:	10 Years

Part No.	Cell Size	C _N [mAh]	I _N [mA]	I _{max.} [mA]
SL350/S	1/2AA	1200	0,6	6
SL350/T	1/2AA	1200	0,6	6
SL350/P	1/2AA	1200	0,6	6
SL361/S	2/3AA	1600	1	10
SL361/T	2/3AA	1600	1	10
SL360/S	AA	2400	2	20
SL360/T	AA	2400	2	20
SL360/P	AA	2400	2	20

C_N = Nominal Capacity, I_N = Nominal Current, I_{max.} = Continuous Discharge Current, max.

Productinformatie

Artikelnummer	SL360/S
Merk	TADIRAN

