
LITHIUM 3.6V 2200MA AA 14.1X50.5MM

€ 6,50

Excl. BTW: € 5,37

Afbeeldingen



Beschrijving

Features

- High energy density
- Long term high performance
- Higher voltage under pulse load even with low background currents
- Improved voltage delay behaviour at ambient and elevated temperatures
- Fast voltage recovery after long term storage
- More capacity
- Higher discharge rate
- No orientation effect
- Wide temperature range from -55°C to +85°C
- SL-_/S: Standard version
- SL-_/T: Solder lugs
- SL-_/P: Axial connection



Technical Specifications



System:	LiSOCl ₂
Nominal Voltage:	3,6V
Temperature Range:	-55...+85°C



Part No.	Cell Size	C _N [mAh]	I _N [mA]	I _{max.} [mA]	I _p [mA]
SL-750/S	1/2AA	1100	1	50	100
SL-761/S	2/3AA	1500	1,3	75	150
SL-760/S	AA	2200	2	100	200
SL-2770/S	C	8500	3	230	400
SL-2780/S	D	19000	4	340	600

C_N = Nominal Capacity, I_N = Nominal Current, I_{max.} = Continuous Discharge Current, max., I_p = Pulse Current Capability

Productinformatie

Artikelnummer	SL760/S
Merk	TADIRAN

