

GESCHAKELDE VOEDING SINGLE OUTPUT 45W 24V/1.88A DIMBAAR

€ 27,95

Excl. BTW: € 23,10

Afbeeldingen



Beschrijving

Features

- Independent control gear
- Plastic housing IP67
- Overload protection by shutdown, auto recovery
- Protected against short circuit, overload
- Built-in PFC circuit
- Low no-load power
- For LED and lighting applications
- Fixed output voltage
- PWM output 1kHz
- Safety standards: EN61347-1 and others
- EMC standards: EN55015, EN61000-3-2, Class C and others
- 3 years manufacturer warranty
- ODLV-45_: 2 in 1 dimming function (0...10V DC and 10V PWM)
- ODLV-45_A: dimmable version and auxiliary voltage output

Technical Specifications

Input Voltage:	90...295V AC (47...63Hz)
	127...417V DC
Input Inrush Current, Max.:	30A
No-load power, less than	
ODLV-45_:	0,5W
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-20...+85°C
Dimensions(LxWxH):	111x77x28,5mm
Weight:	420g

I/P = Input, O/P = Output

Part Nr.	U_A	I_A	P_A	DU_A	h
	[V]	[A]	[W]	[%]	[%]
ODLV-45A-12	12	3	36	10	84
ODLV-45A-24	24	1,88	45,12	10	86
ODLV-45-36	36	1,25	45	10	88
ODLV-45A-36	36	1,25	45	10	88

ODLV-45-48	48	0,94	45,12	10	88
ODLV-45A-48	48	0,94	45,12	10	88
ODLV-45-60	54	0,75	45	10	90
ODLV-45A-60	54	0,75	45	10	90

U_A = Output Voltage, I_A = Output Current, P_A = Output Power, DU_A = Output Voltage Tolerance, h = Typ. Efficiency

Productinformatie

Artikelnummer	ODLV4524
Merk	MEANWELL

