


GESCHAKELDE VOEDING SINGLE OUTPUT 40W 5.0V/8.0A

€ 22,95

Excl. BTW: € 18,97

Afbeeldingen



Beschrijving

Features

- Compact case, 4" x 2"
- Contact pin for nylon-crimp terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low no load power consumption
- Safety standards: UL62368-1, EN62368-1
- EMC standards: EN55032 Class B and more
- 3 years manufacturer warranty
- EPS-45-_: Open frame

Technical Specifications

Input Voltage:

90...264V AC (47...63Hz)

| | |
|-----------------------------|---------------|
| | 127...370V DC |
| Input Inrush Current, Max.: | 60A |
| Leakage Current, Max.: | 2mA |
| Over Load Protection: | 115...160% |
| Withstand Voltage | |
| I/P-O/P: | 3000V AC |
| I/P-FG: | 2000V AC |
| O/P-FG: | 500V AC |
| Operating Temperature: | -30...+70°C |
| Weight | |
| EPS-45-_: | 140g |

I/P = Input, O/P = Output, FG = Frame Ground

| Part Nr. | U_A | I_A | P_A | DU_A | U_{RN} | h |
|------------|-------|----------|-------|--------|----------------------|-----|
| | [V] | [A] | [W] | [%] | [mV _{p-p}] | [%] |
| EPS-45-3.3 | 3,3 | 0...8 | 26,4 | 3 | 80 | 80 |
| EPS-45-5 | 5 | 0...8 | 40 | 2 | 80 | 82 |
| EPS-45-7.5 | 7,5 | 0...5,4 | 40,5 | 2 | 100 | 84 |
| EPS-45-12 | 12 | 0...3,75 | 45 | 2 | 120 | 87 |
| EPS-45-15 | 15 | 0...3 | 45 | 2 | 150 | 88 |
| EPS-45-24 | 24 | 0...1,9 | 45,6 | 1 | 240 | 89 |
| EPS-45-36 | 36 | 0...1,25 | 45 | 1 | 280 | 89 |
| EPS-45-48 | 48 | 0...1 | 48 | 1 | 300 | 90 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

| | |
|---------------|----------|
| Artikelnummer | EPS4505 |
| Merk | MEANWELL |



Productinformatie