


## DIN-RAIL 63MM VOEDING 240W 24V/10A

€ 68,50

Excl. BTW: € 56,61

### Afbeeldingen



### Beschrijving

#### Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- DC OK LED display

## Technical Specifications

Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Typ.:	35A
Leakage Current, Max.:	1mA
Output Voltage Adjustment:	+15%
Over Load Protection:	105...130%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	1000g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
<b>NDR-240-24</b>	24	0...10	240	1	150	88,5
<b>NDR-240-48</b>	48	0...5	240	1	150	90

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

---

Artikelnummer	NDR24024
Merk	MEANWELL

