

ZUIVERE SINUS OMVORMER 24VDC-230VAC 2000W

€ 988,99

Excl. BTW: € 817,35

Afbeeldingen



Beschrijving

Features

- Enclosed design
- Pure sine wave output (THD<3%)
- Peak power up to 4400W
- Adjustable output voltage
- Remote function
- Shutdown when battery is too low
- Alarm function in case of low battery voltage
- Protections: short circuit, overvoltage and overtemperature
- Safety standards: IEC 62368-1; EN 62368-1
- EMC standards: EN55032 Class A
- 3 years manufacturer's warranty

Technical Specifications

| | |
|-----------------------------|---------------------|
| Output voltage, selectable: | 200/220/230/240V AC |
| Output voltage tolerance: | ±3% |
| Output frequency: | 50/60Hz |
| Output frequency tolerance: | ±0,1Hz |

| | |
|-----------------------------|--------------|
| Output power: | 2200W |
| Waveform: | Echt-Sinus |
| Connection type: | EU Typ F |
| Operating temperature range | -25...+70°C |
| Insulation voltage I/P-O/P: | 3000 V AC |
| Insulation voltage O/P-FG: | 1500 V AC |
| Dimensions: | 420x270x98mm |
| Weight: | 8600g |

| Part No | U_{Nenn} | U_E | I_E | η |
|----------------|------------|-----------|-------|--------|
| | [V] | [V] | [A] | [%] |
| NTS-2200-212EU | 12 | 10...16,5 | 250 | 90 |
| NTS-2200-224EU | 24 | 20...33 | 120 | 92 |
| NTS-2200-248EU | 48 | 40...66 | 60 | 93 |

U_{Nenn} = Nominal input voltage, U_E = Input voltage range, I_E = Input current, η = Efficiency

Productinformatie

| | |
|---------------|------------|
| Artikelnummer | NTS2200-24 |
| Merk | MEANWELL |

