

VENTILATOR 5V/DC VAPOLAGER 40X40X6MM 10.7M3/H 39.3DBA PWM

€ 21,78

Excl. BTW: € 18,00

Afbeeldingen



Beschrijving

Motor:	One-phase Single Coil DC Brushless
Nr. of Motor Poles:	4
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-0)
Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	UL1571 AWG28, Stripped, Tinned

Technical Specifications

Rated Voltage:	5V DC
Operating Voltage	
MF40060V11000US99:	4,3...6V DC
Dielectric Strength:	500V AC for 1 Min.
Insulation Resistance at 500V DC :	10MOhm
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C

Part Nr.	U_{Rated}	$P_{Airflow}$	Noise	I	P_{el}	Speed
	[V]	[m ³ /h]	[dBA]	[A]	[W]	[RPM]
MF40060V11000US99	5	10,70	29,3	0,087	0,44	7000

$P_{Airflow}$ = Airflow, P_{el} = Rated Power and Current Tolerance, ±15%

Productinformatie

Artikelnummer	F0504006PA
Merk	SUNON

