

GESCHAKELDE VOEDING 152W QUAD OUTPUT +5/+12/+24/-152 10/4/2/0.6A

€ 129,00

Excl. BTW: € 106,61

Afbeeldingen



Beschrijving

Universal AC input / Full range
Built-in active PFC function, PF>0.95
Protections: Short circuit / Over load / Over voltage
Forced air cooling by built-in DC fan
CH4: Polarity is selectable
Fixed switching frequency at 100KHz

MODEL QP-150D

OUTPUT:
DC VOLTAGE +5V +12V - +24V - -12V

RATED CURRENT 10A - 4A - 2A - 0.6A
CURRENT RANGE 3 ~ 15A - 0 ~ 5A - 0.4 ~ 3A - 0 ~ 1A
RATED POWER 150.2W
RIPPLE & NOISE (max.) 120mVp-p - 150mVp-p - 200mVp-p - 150mVp-p
OUTPUT VOLTAGE ADJ. RANGE CH1: 4.75 ~ 5.5V CH2: 11.4 ~ 13.2V
VOLTAGE TOLERANCE +/-3.0% - +/-3.0% - +/-6% - +/-5.0%
LINE REGULATION +/-1.0% - +/-1.0% - +/-2.0% - +/-1.0%
LOAD REGULATION +/-2.0% - +/-2.0% - +/-6.0% - +/-2.0%
SETUP, RISE TIME 800ms, 50ms/230VAC
HOLD UP TIME (Typ.) 24ms/230VAC at full load

INPUT:

VOLTAGE RANGE 90 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 78%
AC CURRENT (Typ.) 0.75A/230VAC
INRUSH CURRENT (Typ.) COLD START 40A/230VAC
LEAKAGE CURRENT <3.5mA / 240VAC

PROTECTION:

OVER LOAD 105 ~ 150% rated output power
Protection type : Hiccup mode, recovers automatically after fault condition is
OVER VOLTAGE CH1: 5.75 ~ 6.75V CH2: 13.8 ~ 16.2V
Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 199*99*50mm (L*W*H)

Productinformatie

Artikelnummer	QP150D
Merk	MEANWELL
Is on Sale	Nee

