

## ADAPTER 15V 1660MA GESCHAKELD

€ 19,95

Excl. BTW: € 16,49

### Afbeeldingen



### Beschrijving

#### Features

- Plug-in switching power supply
- Universal AC input
- Class II power (without earth pin)
- Compact design
- Overload and short circuit protection
- LED for power on

#### Technical Specifications

- Operating Temperature: 0...+50°C
- storage Temperature: -20...+85°C
- MTBF: 500.000h/25°C
- Dimensions: 79x54x33mm
- Weight: 220g
- Cable Length: 1,8m
- Plug: Coaxial Plug
- Ø2,1 inner(+) x Ø5,5 outer(-)

#### Input

Input Voltage: 90...264V AC (47...63Hz)  
Conducted Inteferece: EN 55022 (B), FCC 15 (B)  
EN61000-3-2,-3-3,-4-2,-4-3,-4-4,-4-5,-4-6,-4-8,-4-11  
Hold Up Time, 115V: 16ms  
In-Rush Current 230V: 40A

Output Voltage, 15V  
Output Voltage Tolerance 3%  
Ripple & Noise, 100mV  
Output Rated Current, 1.66A  
DC Output Power, 25W  
Efficiency, 77%  
All Technical Specifications are Applicable to TU = 25°

## Productinformatie

---

Artikelnummer	PSS1516
Merk	MEANWELL
Is on Sale	Nee

