

## DC-DC CONVERTER 9,2-18V:24V 2.2A IN BEHUIZING

€ 47,50

Excl. BTW: € 39,26

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, screw terminals
- Overload protection, pulsing hiccup shutdown, auto recovery
- Wide input voltage range 2:1
- DC decoupling of input and output
- Input/output insulation 1500V
- Regulated output voltage
- Short-circuit proof

#### Technical Specifications

Input Voltage:	See Table
Over Load Protection:	105...150%
Withstand Voltage	
I/P-O/P:	1500V AC
I/P-FG:	1500V AC
O/P-FG:	500V AC
Operating Temperature:	-10...+60°C
Weight:	480g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	$U_E$	$U_A$	$I_A$	$P_A$	$U_{adj}$	$DU_A$	$U_{RN}$	$h$
	[V]	[V]	[A]	[W]	[V]	[%]	[mV <sub>p-p</sub> ]	[%]
SD-50A-5	9,2...18	5	0...10	50	4,5...5,5	2	100	70
SD-50A-12	9,2...18	12	0...4,2	50,4	11...16	1	120	72
SD-50A-24	9,2...18	24	0...2,1	50,4	23...30	1	150	74
SD-50B-5	19...36	5	0...10	50	4,5...5,5	2	100	73
SD-50B-12	19...36	12	0...4,2	50,4	11...16	1	120	75
SD-50B-24	19...36	24	0...2,1	50,4	23...30	1	150	80
SD-50C-5	36...72	5	0...10	50	4,5...5,5	2	100	76
SD-50C-12	36...72	12	0...4,2	50,4	11...16	1	120	78
SD-50C-24	36...72	24	0...2,1	50,4	23...30	1	150	83

$U_E$  = Input Voltage,  $U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

---

Artikelnummer	SD50A24
Merk	MEANWELL
Is on Sale	Nee



## Productinformatie