

ADAPTER 24V 250MA GESCHAKELD

€ 15,95

Excl. BTW: € 13,18

Afbeeldingen



Beschrijving

Features

- Plug-in switching power supply
- Universal AC input
- Class II power (without earth pin)
- Compact design
- Overload and short circuit protection

Technical Specifications

Operating Temperature: 0...+40°C
Storage Temperature: -20...+85°C
MTBF: 50.000h/25°C
Dimensions: 32x66x42,5mm
Weight: 100g
Cable Length: 1,8m
Plug: Coaxial Plug
Ø2,1 inner(+) x Ø5,5 outer(-)

Input

Input Voltage: 90...264V AC (47...63Hz)
Conducted Interference: EN 55022 (B)
EN61000-3-2,-3-3,-4-2,-4-3,-4-4,-4-5,-4-6,-4-8,-4-11
Hold Up Time, 115V: 16ms

In-Rush Current 230V: 30A

Output Voltage, 24V

Output Voltage Tolerance 2%

Ripple & Noise, 180mV

Output Rated Current, 250mA

DC Output Power, 6W

Efficiency, 80%

All Technical Specifications are Applicable to TU = 25°

Productinformatie

Artikelnummer	PSS2402
Merk	MEANWELL
Is on Sale	Nee

