

## AFGESCHERMD 2X0.22MM2 PLAT BLAUW

€ 1,50

Excl. BTW: € 1,24

### Afbeeldingen



### Beschrijving

#### Specifications

- Conductor drains  $\emptyset$  mm: OFC 20 x 0,12
- Conductor insulation: PE red + transparent
- Conductor insulation: 1,3 ( $\emptyset$  in mm)
- 1st shield: OFC twisted 32 x 0,12
- 2nd shield: -
- Outer isolation: PVC dark blue
- Outer isolation: 2x3 ( $\emptyset$  in mm)

Conductor resistance: 80 Ohm/Km

Shield resistance: 50 Ohm/Km

Cap. Inner conduct. Shield

/ Inner conduct.: 160 pF/m

Working temperature: -20~60 °C (min./max.)

Working Voltage overflash: 30V

Nom Impedance: 35 Ohm

#### Attenuation:

10 MHz: 0,02480 / 90 MHz: 0,28000 / 100 MHz: 0,28530 / 220 MHz: 0,55350 /  
470 MHz: 1,33130 / 770 MHz: 2,21180 / 1000 MHz: 3,0271

## Productinformatie

---

Artikelnummer	AKO2022
Merk	DAP AUDIO
Is on Sale	Nee

