

VOEDING 48V 2500MA GESCHAKELD PLUG R7B 4-POLIG

€ 52,95

Excl. BTW: € 43,76

Afbeeldingen



Beschrijving

Features

- Desktop type
- Universal input
- Standby consumption <0,75W
- Ultra compact design
- Overload and continuous short circuit protection
- High efficiency

Technical Specifications

Operating Temperature: 0...+50°C

Storage Temperature: -20...+85°C

MTBF: 308.900h/25°C

Dimensions: 167x67x35mm

Weight: 520g

Cable Length: 1,2m

Coaxial Plug, Ø2,5 Inner (+) x Ø5,5 Outer (-)

Input

Input Voltage: 90...264V AC (47...63Hz)

Conducted Interference: EN 55022 (B), FCC 15J (B)

EN61000-3-2,-3-3,-4-2,-4-3,-4-4,-4-5,-4-6,-4-8,-4-11

Hold-Up Time, 115V: 50ms

Inrush Current, 230V: 120A

Output Voltage, 48V

Output Voltage Tolerance 2%

Ripple & Noise, 240mV

Output Rated Current, 2.5A

DC Output Power, 120W

Efficiency, 89%

All Technical Specifications are Applicable to TU = 25°

Productinformatie

Artikelnummer	PSS4825
Merk	MEANWELL

