

DC-DC CONVERTER 36-72V:24V 0.625A IN BEHUIZING

€ 20,95

Excl. BTW: € 17,31

Afbeeldingen



Beschrijving

15W Single Output DC-DC Converter

2:1 wide input range

Protections: Short circuit/Over load /voltage

Built-in EMI filter, low ripple noise

100% full load burn-in test

Low cost

High reliability

OUTPUT

DC VOLTAGE: 24V

RATED CURRENT: 0,625A

CURRENT RANGE: 0 ~ 0.625A

RATED POWER: 15W

RIPPLE & NOISE (max.) Note.2: 150mVp-p

VOLTAGE ADJ. RANGE: 21.6 ~ 26.4VDC

VOLTAGE TOLERANCE Note.3: +/- 1.0%

LINE REGULATION: +/- 0.2%

LOAD REGULATION: +/- 0.2%

SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, --12VDC/24VDC/48VDC at full load

INPUT

VOLTAGE RANGE: 36 ~ 72VDC
INPUT EFFICIENCY (Typ.): 78%
DC CURRENT: 0.45A/48VDC

DIMENSION: 78x51x28mm (LxWxH)

Productinformatie

Artikelnummer	SD15C24
Merk	MEANWELL
Is on Sale	Nee

