

DC-DC CONVERTER 36-72V:12V 2.1A IN BEHUIZING

€ 34,50

Excl. BTW: € 28,51

Afbeeldingen



Beschrijving

25W Single Output DC-DC Converter
2:1 wide input range
Protections: Short circuit / Overload / Over voltage
1500VDC I/O isolation
Built-in EMI filter, low ripple noise
100% full load burn-in test
Fixed switching frequency at 83KHz
Low cost
High reliability

OUTPUT

DC VOLTAGE: 12V

RATED CURRENT: 2,1A

CURRENT RANGE: 0 ~ 2.1A

RATED POWER: 25.2W

RIPPLE & NOISE (max.) Note.2: 120mVp-p

VOLTAGE ADJ. RANGE: 11 ~ 16VDC

VOLTAGE TOLERANCE Note.3: +/- 1.0%

LINE REGULATION: +/- 0.3%

LOAD REGULATION: +/- 0.3%

SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, ----- at full load

INPUT

VOLTAGE RANGE: 36 ~ 72VDC

INPUT EFFICIENCY (Typ.): 78%

DC CURRENT: 1.6A/24V

DIMENSION: 99x97x36mm (LxWxH)

Productinformatie

Artikelnummer	SD25C12
Merk	MEANWELL
Is on Sale	Nee

