

POLYPROPYLEEN 680NF 305VAC RM22,5

€ 1,75

Excl. BTW: € 1,45

## Afbeeldingen



## Beschrijving

### Features

- Reliable self-healing
- High degree of interference suppression due to good attenuation and low ESR
- Dielectric: polypropylene (PP) film
- Capacitor electrodes: Vacuum-deposited plastic film

Encapsulation: solvent-resistant, flame-retardent plastic case with epoxy resin seal, UL94V-0  
Terminations: tinned wire

#### Applications

Class X2 RFI applications to meet EMC regulations  
Capacitors connected to the mains between phase and neutral or phase conductors  
Installation category II in accordance with IEC 60664, pulse peak voltage max. 2.5kV

#### Technical Specifications

Rated Voltages (UN): 275V AC  
Capacitance Tolerances:  $\pm 10\%$   
Operating Temperature Range:  $-55\text{...}+105^{\circ}\text{C}$   
Climatic Test Category IEC: 55/105/56/B

Insulation Resistance, Min.  
to incl. 330nF: 15000M $\Omega$   
from 330nF: 5000s  
Failure Rate (40°C, 0,5 x UN): 2,0 fit1)  
Pulse Rise Time, Max. (100V/ $\mu$ s) 425Vss

### Productinformatie

---

Artikelnummer	X2N680
Merk	WIMA
Is on Sale	Nee

