

GESCHAKELDE VOEDING SINGLE OUTPUT 25W 15V/1.7A

€ 22,95

Excl. BTW: € 18,97

Afbeeldingen



Beschrijving

MODEL S-25-15

OUTPUT:

DC VOLTAGE 15.0V

RATED CURRENT 1.7A

CURRENT RANGE 0 ~ 1.7A

RATED POWER 25.5W

RIPPLE & NOISE (max.) 10Vp-p

OUTPUT VOLTAGE ADJ. RANGE 13.5-16.5V

VOLTAGE TOLERANCE +/-1.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%

SETUP, RISE TIME 300ms, 50ms/230VAC

HOLD TIME (Typ.) 90ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY(Typ.) 77%

AC CURRENT (Typ.) 0.35A/230VAC
INRUSH CURRENT (Typ.) COLD START 25A/230VAC
LEAKAGE CURRENT <0.75mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power

Protection type : Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 17.25 ~ 20.25V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 99*97*36mm (L*W*H)

Productinformatie

Artikelnummer	S2515
Merk	MEANWELL
Is on Sale	Nee

