

## GESCHAKELDE VOEDING SINGLE OUTPUT 202W 48V/4.2A

€ 65,16

Excl. BTW: € 53,85

### Afbeeldingen



### Beschrijving

- Universal AC input / full range
- Built-in active PFC function, PF>0.93
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Built-in cooling fan speed control
- Built-in constant current limiting circuit
- Built-in fan speed control
- Remote ON-OFF control(Optional)
- LED indicator for power on
- 100% full load burn-in test
- Fixed switching frequency at PFC:67KHz PWM:134KHz

MODEL SP-200-48

**OUTPUT:**

DC VOLTAGE 48V

RATED CURRENT 4.2A

CURRENT RANGE 0 ~ 4.2A

RATED POWER 201.6W

RIPPLE & NOISE (max.) 250mVp-p

OUTPUT VOLTAGE ADJ. RANGE 45.6 ~ 52.8V

VOLTAGE TOLERANCE +/-1.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%

SETUP, RISE TIME 600ms, 30ms at full load

HOLD TIME (Typ.) 20ms at full load

**INPUT:**

VOLTAGE RANGE 85 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY(Typ.) 84%

AC CURRENT (Typ.) 1.7A/230VAC

INRUSH CURRENT (Typ.) 40A/230VAC

LEAKAGE CURRENT <2mA / 240VAC

**PROTECTION:**

105 ~ 150% rated output power

Protection type : Constant current limiting, recovers automatically after fault condition is removed

OVER VOLTAGE 45.6 ~ 52.8V Protection type : Shut down o/p voltage, re-power on to recover.

Dimensions 199\*99\*50mm (L\*W\*H)

**Productinformatie**

---

Artikelnummer	SP20048
Merk	MEANWELL
Is on Sale	Nee

