

DC-DC CONVERTER 36-72V:12V 12.5A IN BEHUIZING

€ 69,95

Excl. BTW: € 57,81

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Overload protection, current limiting, hiccup after 5s, re-power-on
- Wide input voltage range 2:1
- DC decoupling of input and output
- Input/output insulation 1500V
- Regulated output voltage
- Short-circuit proof

Technical Specifications

Input Voltage:	See Table
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	1500V AC
I/P-FG:	1500V AC
O/P-FG:	500V AC
Operating Temperature:	-10...+60°C
Weight:	860g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_E	U_A	I_A	U_{adj}	DU_A	U_{RN}	h
	[V]	[V]	[A]	[V]	[%]	[mV _{p-p}]	[%]
SD-150B-12	19...36	12	0...12,5	11...16	1	120	75
SD-150B-24	19...36	24	0...6,3	23...30	1	150	77
SD-150C-12	36...72	12	0...12,5	11...16	1	120	77
SD-150C-24	36...72	24	0...6,3	23...30	1	150	80
SD-150D-12	72...144	12	0...12,5	11...16	1	120	79
SD-150D-24	72...144	24	0...6,3	23...30	1	150	82

U_E = Input Voltage, U_A = Output Voltage, I_A = Output Current Range, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	SD150C12
Merk	MEANWELL
Is on Sale	Nee

