
BUTTON ROND BREEK 250V 0.7A ROOD

€ 5,95

Excl. BTW: € 4,92

Afbeeldingen



Beschrijving

General information

Colour of lens opaque red
Form of lens protruding lens
Form of collar round

Dimensions

Overall height 8.2 mm
Diameter of collar 19 mm
Mounting depth 21.5 mm
Mounting hole 15.2 mm

Electrical characteristics

Contact resistance acc. to life max. 300 mΩ
Contact resistance when new max. 50 mΩ
Rated voltage AC max. 250 V
Rated current max. 0.7 A

Mechanical characteristics

Robustness min. 100 N
Operating force max. 7.5 N
Operating travel 3 mm
Switching travel NO 2.0 mm
Switching travel NC ---

Mechanical design
Terminals screw terminals
Mounting ring nut
Illuminability no
Contact arrangement 1 NO
Contact function momentary
Contact system bridge contact
Contact materials Ag
Lamp socket no

Other specifications

Approvals ENEC T 85/55
Ambient temp. operating max. +85 °C
Ambient temp. operating min. -25 °C
Flame class acc. to UL 94 V 0
Weight 7 g
Hot wire ignition acc. to IEC 60695-2-1 yes
Resistance to constant environment according to IEC 600 68-2-3 and 2-30
Storage temperature max. +90 °C
Storage temperature min. -40 °C
Operating life 25000
Degree of protection from front side IP40 (IP65 with sealing cap)
Resistance at variable environment according to IEC 600 68-2-14 and 2-33

Productinformatie

Artikelnummer	RAMR/B
Merk	RAFI
Is on Sale	Nee

